

Floortype High Speed Refrigerated Centrifuge iGL-24MC

Feature

1. With the self-diagnostic and protection system for imbalance, over-speed, over-temperature. Greatly ensured the safe of users and machine.

2. Electric control for both closing and openning door lid, with backup power to avoid power off unexpected, Backup power automatically recharges when machine powered on.

3. Adopt microprocessor control, high efficiency frequency inverter motor, R404a environmentally friendly refrigerant compressor.

- 4. With large 7 Inches color panel show all parameters, and can operate with gloves. .
- 5. With wheels easy to short distance move, and wheels can be fixed.
- 6. Automatic Rotor Identification to avoid over-high speed running of rotor.
- 7. With USB Cord , Data can be stored and download by connecting with PC. (Option function)
- 8. 99 programs can be store, and can set 9 programs for daily use
- 9. When use with swing rotor, the rotor cover can be open with door lid openning, no need to operate by manual.





Parameters

Model	iGL-24MC		
Max Speed	24000r/min		
Max RCF	63070xg		
Max Capacity	6×500ml		
Speed Accuracy	±20r/min		
Temp Range	-20°C~+40°C		
Temp Accuracy	±1°C		
The shortest Acc time	1min30s(0~21000 r/min)	1min35s(0~22000 r/min)	
The shortest Dec time	1min40s(21000 r/min~0)	1min45s(22000 r/min~0)	
Refrigeration system	High-performance Compressor CFC-free Refrigeration System		
Timer Range	0~23h 59min		
Motor	Microprocessor control, Frequency conversion motor		
Noise	≤60dB(A)		
Power Supply	AC220V 50-60Hz 30A		
Dimension	710×820×1200mm(L×W×H)		
Net Weight	260kg		



Rotor

No.1 Angle Rotor		No.2 Angle Rotor	
	Max Speed:24000r/min Max Capacity:12×1.5/2ml Max RCF:63070xg	0	Capacity:16/12×10/15ml Max Speed :21000r/min Max RCF:52300×g
No.3 Angle Rotor		No.4 Angle Rotor	
	Capacity:6×50ml Max Speed :20000r/min Max RCF:43000×g		Capacity:6×70/85ml Max Speed :15000r/min Max RCF:25700×g
No.5 Angle Rotor		No.6 Angle Rotor	
	Capacity:4×250/300ml Max Speed :12000r/min Max RCF:22470×g		Capacity:6×250ml Max Speed :12000r/min Max RCF:22470×g
No.7 Angle Rotor		No.8 Angle Rotor	
	Capacity:8×100ml Max Speed :14000r/min Max RCF:26952×g		Capacity:6×300ml Max Speed :12000r/min Max RCF:22470×g
No.9 Angle Rotor		No.10 Angle Rotor	
	Capacity:6×500ml Max Speed :10000r/min Max RCF:17800×g		Capacity:8×50ml Max Speed :18000r/min Max RCF:37600×g

Note: Rotor and adapters can be customize made

Application







Scientific Research Center Bio-Technology Company

Chemistry Lab

Bío-Pharmaceutícal