

Micro High Speed Refrigerated centrifuge TGL-18/iTGL-18

TGL-18 is useful for routine application in bio-technology, PCR, life science and clinical labs etc. This is suitable for routine sample analysis in Medical, Hospital and Institutional laboratories. With a wide choice of rotor heads and adapters, this unit is truly versatile.

Features

- 1. Stainless steel chamber, compact structure, can can use 8 different capacity rotors.
- 2. Safety Interlock system that prevents opening the centrifuge lid during running.
- 3. 10 programs can be stored, quickly recall the last used program.
- 4. Imbalance sensor, Over speed and over temperature cut off
- 5. Easy operation, LCD touch screen, compressor control.
- 6. Accurate temperature control, range from -20°C~+40°C
- 7. With Emergency lid lock release, in case of power off.





Parameters

Model	TGL-18 (LCD Display)		iTGL-18 (Touch LCD Display)	
Max Speed	18500r/mi ±10r/min	Timer Range		0~99min
Max RCF	19920xg	Motor		Convert motor
Display	LCD touch display	Noise		≤60dB(A)
Max Capacity	36 x1.5/2ml	Power Supply		AC220v&110V 50Hz 18A
Temperature Range	-20°C~+40°C	Dimension		540x340x312mm(L*W*H)
Temperature Accuracy	±1°C	Weight		40kg

Rotors

Itotol 5			
No.1	Max Speed:18500r/min Capacity:12×0.5ml AR Max RCF:19920xg	No.2	Max Speed:16000r/min Capacity:12×1.5/2ml AR Max RCF:17800xg
No.3	Max Speed:14000r/min Capacity:24×1.5/2ml AR Max RCF:18860xg	No.4	Max Speed:16000r/min Capacity:2×8×0.2ml PCR tube Max RCF:15450xg
No.5	Max Speed:11000r/min Capacity:36×1.5/2ml AR Max RCF:10800xg	No.6	Max Speed:16000r/min Capacity:18×0.5ml AR Max RCF:15450xg
No.7	Max Speed:12000r/min Capacity:12/10/8×5ml AR Max RCF:10560xg	No.8	Max Speed:12000r/min Capacity:48×0.5ml Max RCF:11060xg
No.9	Max Speed:15000r/min Capacity:3×8×0.2ml PCR tube Max RCF:14750xg	No.10	Max Speed:13500r/min Capacity:4×8×0.2ml PCR tube Max RCF:11610xg